

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau(43) International Publication Date  
8 January 2004 (08.01.2004)

PCT

(10) International Publication Number  
**WO 2004/002358 A1**(51) International Patent Classification<sup>7</sup>: **A61C 8/00**

60 Göteborg (SE). KULLBERG, Fredrik [SE/SE]; Kristiansborg 120, S-442 75 Lycke (SE).

(21) International Application Number:

PCT/SE2003/000899

(74) Agent: OLSSON, Gunnar; Nobel Biocare AB, Box 5190, S-402 26 Göteborg (SE).

(22) International Filing Date: 4 June 2003 (04.06.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

0201996-6

27 June 2002 (27.06.2002) SE


(71) Applicant (for all designated States except US): NOBEL  
BIOCARE AB [SE/SE]; Box 5190, S-402 26 Göteborg  
(SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): JÖRNÉUS, Lars  
[SE/SE]; Riabergsvägen 7B, S-430 30 Frillesås (SE). JO-  
HANSSON, Anders [SE/SE]; S:t Pauligatan 37 A, S-416(81) Designated States (national): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,  
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,  
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,  
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,  
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,  
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,  
VC, VN, YU, ZA, ZM, ZW.(84) Designated States (regional): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),  
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),  
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,  
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

[Continued on next page]

(54) Title: SPACER PREFERABLY MADE ENTIRELY OF CERAMIC AND WITH AN ADAPTER



(57) Abstract: A spacer (3) with associated adapter (4) is designed to be fitted on an implant (1). The adapter comprises first and second portions (4b, 4c) designed to cooperate with the spacer and the implant, respectively, for securing the spacer on the implant. The adapter is completely enclosed by the spacer and the implant, and the first portion of the adapter can be designed with slits for forming resilient elements on said portion and/or with penetrating parts which, when the adapter and the spacer are joined together, are deformed as it penetrates into opposite parts in the spacer material. The spacer and the adapter can in this way be easily held together upon application to the implant and can be taken apart when completion work is performed on the spacer.

WO 2004/002358 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*